

Construction specifications

Product	Air
Style Number	T7984
Fiber Content*	100% Universal Fibers® Type 6,6 nylon with Permanent Stain Resist
Fiber Weight (tufted)	16 oz./ Sq. Yd. (542 g/m ²)
Construction	Patterned Loop
Gauge	1/12
Carpet Tile Size	12"W x 36"L (30.48cm x 91.44cm)
Dye Method	Solution Dyed
Pile Height	.250"/.125" (6.35mm/3.18mm)
Total Thickness	.281" (7.14mm)
Total Weight	102.28 oz./ Sq. Yd. (3468 g/m ²)
Primary Backing	Synthetic
Secondary Backing	EarthWise
GLP Certification	GLP1922

*Also offered using Thrive® by Universal Fibers® with 75% recycled content, nylon 6,6. Contact your Masland representative for pricing and information.

Specifications may vary slightly over the life of a product. For current specifications, please visit www.maslandcontract.com.

Performance specifications

Warranty	Lifetime Commercial Limited Warranty
Flammability Rating	Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM ² Class 1 (EU) BFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
Smoke Density	Passes NBS Smoke Chamber Test ASTM E-662 (flaming mode)
Colorfastness to Light	4.0 or better
Static Rating	Less than 3.5 kV. Antistat warranted for the life of the carpet

Air meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program.

Air is 3rd party certified to the NSF-140 Sustainable Carpet Standard.

Slight variations between sample swatches and production goods are to be expected and are considered normal. Likewise, such variations will occur between production goods of different dye lots. Masland laboratory matches are obtained under cool white fluorescent lighting. Chair pads are recommended to enhance the aesthetic value and longevity of the product.

All Masland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of Federal Law.



Construction specifications

Product	Earth
Style Number	T7985
Fiber Content*	100% Universal Fibers® Type 6,6 nylon with Permanent Stain Resist
Fiber Weight (tufted)	16 oz./ Sq. Yd. (542 g/m ²)
Construction	Patterned Loop
Gauge	1/12
Carpet Tile Size	12"W x 36"L (30.48cm x 91.44cm)
Dye Method	Solution Dyed
Pile Height	.250"/.125" (6.35mm/3.18mm)
Total Thickness	.281" (7.14mm)
Total Weight	102.28 oz./ Sq. Yd. (3468 g/m ²)
Primary Backing	Synthetic
Secondary Backing	EarthWise
GLP Certification	GLP1922

*Also offered using Thrive® by Universal Fibers® with 75% recycled content, nylon 6,6. Contact your Masland representative for pricing and information.

Specifications may vary slightly over the life of a product. For current specifications, please visit www.maslandcontract.com.

Performance specifications

Warranty	Lifetime Commercial Limited Warranty
Flammability Rating	Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM ² Class 1 (EU) BFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
Smoke Density	Passes NBS Smoke Chamber Test ASTM E-662 (flaming mode)
Colorfastness to Light	4.0 or better
Static Rating	Less than 3.5 kV. Antistat warranted for the life of the carpet

Earth meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program.

Earth is 3rd party certified to the NSF-140 Sustainable Carpet Standard.

Slight variations between sample swatches and production goods are to be expected and are considered normal. Likewise, such variations will occur between production goods of different dye lots. Masland laboratory matches are obtained under cool white fluorescent lighting. Chair pads are recommended to enhance the aesthetic value and longevity of the product.

All Masland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of Federal Law.

Construction specifications

Product	Fire
Style Number	T7986
Fiber Content*	100% Universal Fibers® Type 6,6 nylon with Permanent Stain Resist
Fiber Weight (tufted)	16 oz./ Sq. Yd. (542 g/m ²)
Construction	Patterned Loop
Gauge	1/12
Carpet Tile Size	12"W x 36"L (30.48cm x 91.44cm)
Dye Method	Solution Dyed
Pile Height	.250"/.125" (6.35mm/3.18mm)
Total Thickness	.281" (7.14mm)
Total Weight	102.28 oz./ Sq. Yd. (3468 g/m ²)
Primary Backing	Synthetic
Secondary Backing	EarthWise
GLP Certification	GLP1922

*Also offered using Thrive® by Universal Fibers® with 75% recycled content, nylon 6,6. Contact your Masland representative for pricing and information.

Specifications may vary slightly over the life of a product. For current specifications, please visit www.maslandcontract.com.

Performance specifications

Warranty	Lifetime Commercial Limited Warranty
Flammability Rating	Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM ² Class 1 (EU) BFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
Smoke Density	Passes NBS Smoke Chamber Test ASTM E-662 (flaming mode)
Colorfastness to Light	4.0 or better
Static Rating	Less than 3.5 kV. Antistat warranted for the life of the carpet

Fire meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program.

Fire is 3rd party certified to the NSF-140 Sustainable Carpet Standard.

Slight variations between sample swatches and production goods are to be expected and are considered normal. Likewise, such variations will occur between production goods of different dye lots. Masland laboratory matches are obtained under cool white fluorescent lighting. Chair pads are recommended to enhance the aesthetic value and longevity of the product.

All Masland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of Federal Law.



Construction specifications

Product	Water
Style Number	T7987
Fiber Content*	100% Universal Fibers® Type 6,6 nylon with Permanent Stain Resist
Fiber Weight (tufted)	16 oz./ Sq. Yd. (542 g/m ²)
Construction	Patterned Loop
Gauge	1/12
Carpet Tile Size	12"W x 36"L (30.48cm x 91.44cm)
Dye Method	Solution Dyed
Pile Height	.250"/.125" (6.35mm/3.18mm)
Total Thickness	.281" (7.14mm)
Total Weight	102.28 oz./ Sq. Yd. (3468 g/m ²)
Primary Backing	Synthetic
Secondary Backing	EarthWise
GLP Certification	GLP1922

*Also offered using Thrive® by Universal Fibers® with 75% recycled content, nylon 6,6. Contact your Masland representative for pricing and information.

Specifications may vary slightly over the life of a product. For current specifications, please visit www.maslandcontract.com.

Performance specifications

Warranty	Lifetime Commercial Limited Warranty
Flammability Rating	Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM ² Class 1 (EU) BFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
Smoke Density	Passes NBS Smoke Chamber Test ASTM E-662 (flaming mode)
Colorfastness to Light	4.0 or better
Static Rating	Less than 3.5 kV. Antistat warranted for the life of the carpet

Water meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program.

Water is 3rd party certified to the NSF-140 Sustainable Carpet Standard.

Slight variations between sample swatches and production goods are to be expected and are considered normal. Likewise, such variations will occur between production goods of different dye lots. Masland laboratory matches are obtained under cool white fluorescent lighting. Chair pads are recommended to enhance the aesthetic value and longevity of the product.

All Masland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of Federal Law.

