

**Construction specifications**

---

<b>Product</b>	Rough
<b>Style Number</b>	T7988
<b>Fiber Content*</b>	100% Universal Fibers® Type 6,6 nylon with Permanent Stain Resistance
<b>Fiber Weight (tufted)</b>	16 oz./ Sq. Yd. (542 g/m <sup>2</sup> )
<b>Construction</b>	Patterned Loop
<b>Gauge</b>	1/12
<b>Carpet Tile Size</b>	12"W x 36"L (30.48cm x 91.44cm)
<b>Dye Method</b>	Solution Dyed
<b>Pile Height</b>	.250"/.188" /.125" (6.35mm/4.78mm/3.18mm)
<b>Total Thickness</b>	.310" (7.87mm)
<b>Total Weight</b>	101 oz./ Sq. Yd. (3425 g/m <sup>2</sup> )
<b>Primary Backing</b>	Synthetic
<b>Secondary Backing</b>	EarthWise
<b>GLP Certification</b>	GLP1922

Product manufactured utilizing pre-consumer and post-consumer recycled content. Please see environmental specifications for additional information.

\*Also offered using Thrive® by Universal Fibers® with 75% recycled content, nylon 6,6. Contact your Masland representative for pricing and information.

Specifications may vary slightly over the life of a product. For current specifications, please visit [www.maslandcontract.com](http://www.maslandcontract.com).

**Performance specifications**

---

<b>Warranty</b>	Lifetime Commercial Limited Warranty
<b>Flammability Rating</b>	Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM <sup>2</sup> Class 1 (EU) BFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
<b>Smoke Density</b>	Passes NBS Smoke Chamber Test ASTM E-662 (flaming mode)
<b>Colorfastness to Light</b>	4.0 or better
<b>Static Rating</b>	Less than 3.5 kV. Antistat warranted for the life of the carpet

Rough meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program. Rough is 3<sup>rd</sup> party certified to the NSF-140 Sustainable Carpet Standard.

Slight variations between sample swatches and production goods are to be expected and are considered normal. Likewise, such variations will occur between production goods of different dye lots. Masland laboratory matches are obtained under cool white fluorescent lighting. Chair pads are recommended to enhance the aesthetic value and longevity of the product.

All Masland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of Federal Law.



**Construction specifications**

---

<b>Product</b>	Tumble
<b>Style Number</b>	T7989
<b>Fiber Content*</b>	100% Universal Fibers® Type 6,6 nylon with Permanent Stain Resistance
<b>Fiber Weight (tufted)</b>	16 oz./ Sq. Yd. (542 g/m <sup>2</sup> )
<b>Construction</b>	Patterned Loop
<b>Gauge</b>	1/12
<b>Carpet Tile Size</b>	12"W x 36"L (30.48cm x 91.44cm)
<b>Dye Method</b>	Solution Dyed
<b>Pile Height</b>	.250"/.188" / .125" (6.35mm/4.78mm/3.18mm)
<b>Total Thickness</b>	.310" (7.87mm)
<b>Total Weight</b>	101 oz./ Sq. Yd. (3425 g/m <sup>2</sup> )
<b>Primary Backing</b>	Synthetic
<b>Secondary Backing</b>	EarthWise
<b>GLP Certification</b>	GLP1922

Product manufactured utilizing pre-consumer and post-consumer recycled content. Please see environmental specifications for additional information.

\*Also offered using Thrive® by Universal Fibers® with 75% recycled content, nylon 6,6. Contact your Masland representative for pricing and information.

Specifications may vary slightly over the life of a product. For current specifications, please visit [www.maslandcontract.com](http://www.maslandcontract.com).

**Performance specifications**

---

<b>Warranty</b>	Lifetime Commercial Limited Warranty
<b>Flammability Rating</b>	Flooring Radiant Panel ASTM E-648 and/or NFPA 253 Greater than 0.45 watts/CM <sup>2</sup> Class 1 (EU) BFL S 1 Surface Flammability of Carpets and Rugs (16 CFR Chapter II Subchapter D, Part 1630 CPSC FF 1-70) also referenced as ASTM D-2859
<b>Smoke Density</b>	Passes NBS Smoke Chamber Test ASTM E-662 (flaming mode)
<b>Colorfastness to Light</b>	4.0 or better
<b>Static Rating</b>	Less than 3.5 kV. Antistat warranted for the life of the carpet

Tumble meets the standards for the Carpet & Rug Institute's Indoor Air Quality Green Label Plus Carpet Testing Program. Tumble is 3<sup>rd</sup> party certified to the NSF-140 Sustainable Carpet Standard.

Slight variations between sample swatches and production goods are to be expected and are considered normal. Likewise, such variations will occur between production goods of different dye lots. Masland laboratory matches are obtained under cool white fluorescent lighting. Chair pads are recommended to enhance the aesthetic value and longevity of the product.

All Masland designs are protected under the U.S. Copyright Act of 1976. Any unauthorized duplication or approximation of a Masland design constitutes copyright infringement in violation of Federal Law.

